

## A: Datasheet

Algorithm: neurotechnology\_010

Developer: Neurotechnology

Submission Date: 2022\_01\_07

Investigation:

Frontal mugshot ranking 19 (out of 329) -- FNIR(1600000, 0, 1) = 0.0012 vs. lowest 0.0009 from sensetime\_006

Mugshot webcam ranking 26 (out of 291) -- FNIR(1600000, 0, 1) = 0.0094 vs. lowest 0.0057 from sensetime\_006

Mugshot profile ranking 14 (out of 260) -- FNIR(1600000, 0, 1) = 0.0702 vs. lowest 0.0550 from sensetime\_006

Immigration visa–border ranking 5 (out of 218) -- FNIR(1600000, 0, 1) = 0.0013 vs. lowest 0.0009 from sensetime\_006

Immigration visa–kiosk ranking 12 (out of 215) -- FNIR(1600000, 0, 1) = 0.0684 vs. lowest 0.0487 from cubox\_000

Identification:

Frontal mugshot ranking 37 (out of 329) -- FNIR(1600000, T, L+1) = 0.0098, FPIR=0.001000 vs. lowest 0.0017 from nec\_005


Mugshot webcam ranking 38 (out of 289) -- FNIR(1600000, T, L+1) = 0.0369, FPIR=0.001000 vs. lowest 0.0120 from nec\_005

Mugshot profile ranking 9 (out of 259) -- FNIR(1600000, T, L+1) = 0.2770, FPIR=0.001000 vs. lowest 0.1331 from cloudwalk\_hr\_000


Immigration visa–border ranking 28 (out of 217) -- FNIR(1600000, T, L+1) = 0.0101, FPIR=0.001000 vs. lowest 0.0032 from paravision\_009

Immigration visa–kiosk ranking 20 (out of 212) -- FNIR(1600000, T, L+1) = 0.1271, FPIR=0.001000 vs. lowest 0.0728 from paravision\_009


B: Mugshot natural images, identification mode: FNIR(N, L+1, T) vs. most accurate (nec\_005)



C: Evolution of accuracy for NEUROTECHNOLOGY algorithms on three datasets 2018 – present




D: 1:N error tradeoff by dataset and enrollment type. N = 1600000 individuals




E: Dependence of error rates on T by number enrolled identities, N, for Mugshot natural images


N 00640000 01600000 03000000 06000000 12000000



F: FPIR vs. Selectivity for mugshot images, N = 1600000 subjects enrolled with one recent mate




G: FPIR dependence on T by probe type for N = 1600000 subjects




#### H: Reduced length candidate lists for human review

Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




# I: FNIR and FPIR dependence on threshold


Dataset is border–border with time–lapse [10,15] YRS with N = 1600000. Probes are 10–15 years later than enrollment image




J: DET for Mugshot natural images and various N. Links connect points of equal threshold.



K: Investigational mode: FNIR(N, 1, 0) vs. most accurate (sensetime\_006)



L: Investigational mode: FNIR(1600000, R, 0) by probe type





M: Template duration; search duration vs. N. The blue and pink ribbon covers 95 percent of observed measurements.  
The template generation time is independent of N. The log and power-law models are fit to the first two (N,T) observations

Search Duration (milliseconds)

Enrolled population size, N, one image per person


O: FNIR(T, N = 1.6 million) by sex, age and time-lapse. The top row gives investigational rank-1 miss rates.  
 The bottom panels give high threshold for more lights-out identification with low FPIR.

Algorithm: neurotechnology\_010, Dataset: Border–Crossing Ageing N = 1600000  
 Text encodes FNIR, Color encodes log(FNIR)





P: FPIR(N = 1.6 million) by sex and age. It is typical for false positive identification rates to be higher in women except in their teens.

Algorithm: neurotechnology\_010, Dataset: Border–Crossing Ageing  
Threshold: 2171.000000 set to achieve FPIR(30–45, Male) = 0.001



Q: Identification FNIR(N, T, L+1) and Investigational FNIR(N, 0, R) under ageing

Dataset: 2018 Mugshot N = 3068801



R: Decline of genuine scores with ageing, with some eventually dropping below typical thresholds shown by the horizontal lines

